

# Coating Thickness Gauge - PCE-CT 26FN



## Product Info :

**Coating Thickness Gauge PCE-CT 26FN** manufacturers and suppliers have been dedicated to provide the best instrument to the industries for the purpose of measuring the thickness of the coatings that are applied to different surfaces. In the industries, there are different types of coatings used for protection of different products and surfaces. This ensures that the quality of the products is greatly dependent on the coatings that are applied to them as these coatings protect them from the factors such as dust, moisture and so forth. Due to this reason, the manufacturers of these coatings as well as the manufacturers of the products to which these coatings are applied, need to ensure that the coating material is of the best quality and hence is capable of providing the best level of protection to the surfaces. The manufacturers need to measure the thickness of the coating with great accuracy for better quality assurance.

Pacorr has made its place in list of the best Coating Thickness Gauge PCE-CT 26FN manufacturers and suppliers that provide the best precision testing instruments that are used for ensuring the best quality coating products delivered to the industries. The industries such as paints and varnishes, automobile industries and so forth, have a great involvement of paints and coating in their production process as they need them to protect the surfaces of their products from various external threats such as dust, dirt, moisture and corrosion. Additionally, these coatings are also used for enhancing the aesthetic appeal of the final products. As the protection of the surfaces is solely dependent on the quality of the coatings, it is essential for the manufacturers to ensure the best quality of coatings and paint products that are delivered to the customers.

## TECHNICAL DATA :

- Measuring range 0 ... 1250  $\mu\text{m}$  (0 ... 50 mils)
- Resolution 1  $\mu\text{m}$  (0.1 mils)
- Accuracy  $\pm (3\% + 2 \mu\text{m})$  or  $\pm (3\% + 0.1 \text{ mils})$
- Smallest measuring surface 5 x 5 mm
- Smallest radius of curvature Convex, 3 mm / concave: 50 mm
- Smallest thickness of the base material Fe: at least 0.5 mm
- NFe: at least 0.3 mm
- Display OLED display
- Ambient temperature 0 ... 50°C / 32 ... 120°F
- Power supply 2 x AAA battery 1.5V
- Dimension 100 x 52 x 29 mm / 4 x 2 x 1.1 in
- Weight About 68 g / < 1 lb (without batteries)

## FEATURES :

- Comes with a sturdy carrying case for easy handling
- Very easy operation and handling
- Sturdy design for safety in harsh industrial conditions.

## Our Valuable Customer



Pacorr Testing Instruments Pvt. Ltd.

11/15, Site-4 Industrial Area, Sahibabad, Ghaziabad- 201010 Contact No: +91-8882149230, Email Id: info@pacorr.com